16/181

SPECIFICATION SHEET

GH27GM-90RPM
(HN-GH12-1324Y)

DATE: FEB.09,99'.
NO.: HN99020902
PAGE: 2/2

CUSTOMER NAME:
TYPE: HN-GH27GM TYPE
MODEL NO.: HN-GH12-1324Y
CUSTOMER PART NO.:

II. SPECIFICATIONS:

1. RATED VOLTAGE: DC 12V

2. DC VOLTAGE OPERATING RANGE: DC 4.5 - 12V

3. TORQUE (LOAD) AT MAXIMUM EFFICIENCY : 450 g-cm

4. STALL TORQUE: 750g-cm

5. NO LOAD SPEED: 84RPM +/-10%

6. SPEED AT MAXIMUN EFFICIENCY (UNDER LOAD AT 450g-cm): 73RPM +/- 10%

7. NO LOAD CURRENT: MAX. 55 mA

8. CURRENT AT MAX. EFFICIENCY (UNDER LOAD AT 450 g-cm): MAX. 115 mA

9. SHAFT END PLAY: MAX. 0.8m/m

10 INSULATION RESISTANCE: 10M OHM

11. DIELECTRIC STRENGTH: 300V DC

12. GEAR RATIO: 70:1

SPECIFICATION SHEET

DATE: FEB.09,99'
NO.: HN99020902
PAGE: 1/2

CUSTOMER NAME:
TYPE: HN-GH27GM TYPE
MODEL NO.: HN-GH12-1324Y
CUSTOMER PART NO.:

I. OUTTER DIMENSIONS :



GEAR RATIO: 70:1, ALLOWABLE TORQUE: 0.7 KG-CM, EFFICIENCY: 66%